

The vehicle in the photographs include optional equipments, special coloring and processing.

Tailgate Lifter Swing type

Standard equipments

Power unit

Low noise power unit and controller are accomodated in a highly durable stainless box.



3m cable remote controller

Operation can be done while checking condition of cargo on a platform.




Specifications

| Model | | | S600 | S800 | S1000 |
|----------------------------------|--------|------|-------------|-----------|-------|
| Max lifting capacity | | (kg) | 600 | 800 | 1,000 |
| Max body deck ground height (mm) | | | 700~1,150 | 750~1,200 | |
| Platform dimensions | Length | (mm) | 850 | | 1,000 |
| | Width | (mm) | 1,490~2,260 | | |
| Lifting time (sec.) | | 4~18 | | | |
| Lowering time (sec.) | | 4~18 | | | |

The above mentioned figures are approximate.

Structure diagram



Note: Specifications and the other contents on this catalogue are subject to change without prior notice due to product improvement. Product photos on this catalogue might include optional devices.

Kyokuto Kaihatsu Kogyo Co., Ltd.

TOKYO OFFICE 3-15-10 ,Higashi-shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan Telephone : +81(3)5781-9828 Facsimile : +81(3)5781-3438 E-mail : web-overseas@kyokuto.com http://www.kyokuto.com/